


SWING
DECLARATION OF PERFORMANCE

IN ACCORDANCE WITH CONSTRUCTION PRODUCTS REGULATION (EU) NO. 305/2011
DOP 24010A

1. Unique identification code of the product-type: Pre-lacquered veneered wooden floor covering with surface coating (groups below) / EN 14342 - EN 14354
2. Type, batch or serial number or any other element allowing identification of the construction product: Parky Swing
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: The products are intended for use as floor coverings(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 14342
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): Decospan N.V., Lageweg 33, B-8930 Menen, Belgium. Produced at same location.
5. Name and contact address of the authorised representative: Not applicable
6. System or systems of assessment and verification of constancy of performance of the construction product: AVCP 3 (of Appendix ZA.2 of EN 14342 : 2013)
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard. Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports.
 - Determination of reaction to fire according (EN 13501-1):
Centexbel: NB0493, Technologiepark 70, 9052 Gent Belgium, Test reports 20.06759.01 and 20.06759.02
 - Determination of formaldehyde emissions according (EN 16516):
Eurofins product testing A/S, Smedeskovvej 38, 8464 Galten Denmark, Test reports 392-2023-00570801_A_EN
 - Determination of the slip resistance:
Wood.be, Hof ter Vleestdreef 3, 1070 Anderlecht Belgium, Test report 200034/1
 - Determination of the thermal conductivity (EN 12667):
Wood.be, Hof ter Vleestdreef 3, 1070 Anderlecht Belgium, Test reports 180646/6; 180646/4
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: Not applicable
9. Declared performance: EN14342: 2013 Wood Flooring

Product	PARKY SWING
Mean Density	850 kg/m ³
Total Thickness	10 mm
Backing	Veneer
Reaction to fire (EN13501-1)	Class Cfl-s1
Formaldehyde Emission (EN 717-1)	Class E1
Content PCP (EN 14342)	<5 ppm
Slip resistance (CEN/TS 15676)	≥45 USRV
Thermal conductivity (EN 12667)	0.14 W/m*K
Biological durability (EN 335)	Class 1
Dimensions	593×121×10 mm
Installation method	Floating installation



Pieterjan Desmet
C.E.O.

Date: 24/02/2025