


## General

Toplayer	Thickness: 2mm (5/64 inch)
Dimensions	Length: 1185mm (46 5/8 inch)
	Width: 150mm (6 inch)
	Thickness: 10mm (3/8 inch)
Core	High Density Fibreboard (HDF)
Bevels	2 bevels (2x0.5mm)
Gloss	Matt (10)
Structure	Brushed
Backing	Real wood
Density	>850kg/m³
Weight/sqm	8kg
Connection system	Uniclic
Installation type	Floating
Standard colors	<u>Trendy Oaks</u> : European, Ivory, Essence, Umber, Milk, Desert

## Product composition



## Technical specifications

Domestic Usage Classification	22
Commercial Usage Classification	31
CE Certification	EN14342:2005+A1:2008
Warranty	15 years
Formaldehyde Emission	E1
PCP	PCP free
Underfloor heating	ok but glued
Thermal resistance	0,07m²K/W
Thermal conduction	0,14W/mK
Fire reaction & smoke generation	Dfl-s1
Maintenance	Weekly cleaning with 'Par-ky wood floor cleaner'

## Packaging

Box	9 boards
	Surface 1,60m² (17.22 sq.ft)
	Gross Weight 13,5kg (29.76 lbs)
Pallet	66 boxes
	Surface 105,6m² (1136.67 sq.ft)
	Gross weight 910kg (2006.21 lbs)

