


General

Toplayer	Thickness: 2mm (5/64inch)
Dimensions	Length: 1935mm (76 1/8 inch)
	Width: 194mm (7 41/64 inch)
	Thickness: 12mm (15/32 inch)
Core	High Density Fibreboard (HDF)
Bevel	2 bevels (2x0.5mm)
Gloss	Matt (10)
Structure	Brushed
Backing	Real Wood + Cork
Density	>850kg/m ³
Weight/sqm	10kg
Connection system	Uniclic
Installation type	Floating
Standard Colors	<u>Trendy Oaks</u> : Essence, Ivory, Desert

Product composition



Technical specifications

Domestic Usage Classification	22
Commercial Usage Classification	31
CE Certification	EN14342:2005+A1:2008
Warranty	15 years
Formaldehyde Emission	E1
PCP	PCP free
Underfloor heating	ok but glued
Thermal resistance	0,100m ² K/W
Thermal conduction	0,11W/mK
Fire reaction & smoke generation	Dfl-s1
Maintenance	Weekly cleaning with 'Par-ky wood floor cleaner'

Packaging

Box	6 boards
	Surface 2,252m ² (24.24 sq.ft)
	Gross weight 18,80kg (41.45 lbs)
Pallet	50 boxes
	Surface 112,60m ² (1212.02 sq.ft)
	Gross weight 960kg (2116.44 lbs)

