

## CE declaration of Performance (DoP)

Issued in accordance with the construction products directive (CPD)

Nr; 15012

This is to certify that in compliance with the Council Directive 89/106/EEC of 21<sup>st</sup> December 1988 on construction products, as amended.

Decospan N.V., Lageweg 33, B-8930 Menen, Belgium

Produced at same location.

Declares that the product detailed below conform to type as required by the above Directives as evidenced by the conformity Route below under attestation system 3 of Appendix ZA.2 of EN 14342 : 2013

Applied Harmonized Standards ; EN14342 : 2013 Wood Flooring

Characteristic	Standard	Performance declaration
Reaction to fire	Linked with the mean density	Dfl-sl 850 kg/m <sup>3</sup>
	Linked with the minimum overall thickness	12 mm
Emission of formaldehyde	EN 717-1	E1
Content of PCP	CEN/TR 14823	< 5 ppm
Breaking strength	EN 1533	NPD
Slipperiness	EN 1339 Annex J	NPD
Thermal conductivity	EN 12664	0.12 W/mK
Biological durability	EN 335	Class 1

Notified Body: CTIB-TCHN, Hof ter Vleest Dreef 3, B-1070 Brussels, Belgium

Manufacturer's product : Decospan N.V.

with specifications;

- 1935 x 195 x 12 mm
- HDF core with 2 sides of veneer
- Finished with ±100 g/m<sup>2</sup> UV- lacquer
- Pre-lacquered veneer wooden flooring
- Floating installation for indoor use

Standards applicables; EN 14342, EN 14354 (Wood veneer floor coverings)

Jan Desmet

C.E.O.

Date: 01/01/2016