


## General

Top layer	Thickness: 0.6mm (1/32 inch)
Dimensions	Length: 1203mm (47 3/8 inch)
	Width: 124mm (4 7/8 inch)
	Thickness: 8.3mm (5/16 inch)
Core	High Density Fibreboard (HDF)
Bevel	Brushed: 4 bevels (4x0.5mm) – Sealed: 2 bevels (2x0.5mm)
Gloss	Brushed: Super Matt (3) – Sealed: Satin (20)
Structure	Brushed– Sealed
Backing	Real wood
Density	850kg/m <sup>3</sup>
Weight/sqm	8kg
Connection system	Uniclic
Installation type	Floating
Standard colors	<u>Walnuts</u> : Smoked Walnut
	<u>Character Woods</u> : Cotton Triba, Teak, Rosewood Santos, Bamboo Steamed, Jatoba

## Product composition



## Technical specifications

Domestic Usage Classification	23
Commercial Usage Classification	33
CE Certification	EN14342:2013
Warranty	Residential limited lifetime warranty Commercial use: 10 years
Formaldehyde Emission	E1
PCP	PCP free
Underfloor heating	High suitability, with a thermal resistance of 0.059m <sup>2</sup> K/w there is a minimal waste of energy.
Thermal resistance	0,059m <sup>2</sup> K/W
Thermal conduction	0,14W/mK
Fire reaction & smoke generation	Cfl-s1
Maintenance	Weekly cleaning with 'Parky wood floor cleaner'

## Packaging

Box	11 boards Surface 1,641m <sup>2</sup> (17.66 sq.ft) Gross weight 11,75kg (25.90 lbs)
Pallet	77 boxes Surface 126,36m <sup>2</sup> (1360 sq.ft) Gross weight 918,75kg (2026 lbs)

