

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

PIGMENTED LAQUER PEN 240

UFI:

5FJ7-K0PN-A00N-K74K

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Covering agent in writing tool or marker pen

Uses advised against

No data available.

1.3 Supplier of the Safety Datasheet

Distributor of the product

Decospan NV
Lageweg 33
B-8930 Menen - Belgium
tel.no. +32 56 52 88 00
email: info@decospan.com

1.4 Emergency telephone number

+32 70 245 245 (National Poisons Information Centre)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eye Irrit. 2; H319

Flam. Liq. 2; H225

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07

Signal word

Danger

Hazardous component(s) to be indicated on label:

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

1-ethoxypropan-2-ol

Hazard statement(s)

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container to a facility in accordance with local/regional/national/international regulations.

UFI:

5FJ7-K0PN-A00N-K74K

2.3 Other hazards

PBT assessment
No data available.
vPvB assessment
No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	ethanol		
	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 70,00 - < 90,00 wt%
2	1-ethoxypropan-2-ol		
	1569-02-4 216-374-5 603-177-00-8 -	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10,00 - < 25,00 wt%
3	1-methoxy-2-propanol		
	107-98-2 203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336	< 5,00 wt%
4	A mixture of: tert-alkyl(C12-C14)ammonium bis[1-[(2-hydroxy-5-nitrophenyl)azo]-2-naphthalenolato(2-)]-chromate(1-), tert-alkyl(C12 C14)ammonium ((1-(4(or 5)-nitro-2-oxidophenylazo)-2-		

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

	naphtholato)(1-(3 nitro-2-oxido-5-pentylphenylazo)-2-naphtholato)chroma			
	117527-94-3 403-720-7 611-044-00-0 -	Aquatic Chronic 2; H411	< 2,50	wt%
5	hydrogen hydroxy[2-hydroxy-3-[(2-hydroxy-3-nitrobenzylidene)amino]-5-nitrobenzenesulphonato(3-)]chromate(1-), compound with 3-[(2-ethylhexyl)oxy]propylamine (1:1)			
	85455-32-9 287-267-9 - -	Eye Irrit. 2; H319 Aquatic Chronic 3; H412	< 2,50	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	Eye Irrit. 2; H319: C >= 50%	-	-

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. In case of persisting adverse effects, consult a physician.

After inhalation

Remove affected persons from dangerous area by observing suitable respiratory protection measures. Ensure supply of fresh air.

After skin contact

In case of contact with skin wash off with water. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Get medical attention if pain still persists.

After ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Containers close to fire should be transferred to a safe place. Cool closed containers exposed to fire with water. Do not inhale explosion and/or combustion byproducts.

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Keep away from ignition sources. Ensure adequate ventilation.

For emergency responders

Personal protective equipment (PPE) - see section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

Information regarding safe handling, see section 7. Information regarding personal protective measures, see section 8. Information regarding waste disposal, see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Do not inhale vapours. Avoid contact with eyes and skin. Wash hands before breaks and after work. Remove contaminated clothing and shoes and launder thoroughly before reusing.

Advice on protection against fire and explosion

Keep away from ignition sources and provide for good ventilation. Isolate from sources of heat, sparks and open flame. Take precautionary measures against electrostatic loading (earthing necessary during loading operations). Use explosion-proof equipment/fittings and non-sparking tools. Vapours can form an explosive mixture with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original. Provide floor trough without outlets.

Incompatible products

Substances to be avoided, see section 10.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
	List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)		
	Ethanol		
	WEL short-term (15 min reference period)		1000 ppm
2	1-methoxy-2-propanol	107-98-2	203-539-1
	2000/39/EC		

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

	1-Methoxypropanol-2				
	WEL short-term (15 min reference period)	568	mg/m ³	150	ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m ³	100	ppm
	Skin resorption / sensibilisation	Skin			
List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)					
	Propylene glycol monomethyl ether				
	WEL short-term (15 min reference period)	568	mg/m ³	150	ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m ³	100	ppm
	Comments	IOELV			
3	A mixture of: tert-alkyl(C12-C14)ammonium bis[1-[(2-hydroxy-5 nitrophenyl)azo]-2-naphthalenolato(2-)]-chromate(1-), tert-alkyl(C12 C14)ammonium ((1-(4(or 5)-nitro-2-oxidophenylazo)-2-naphtholato)(1-(3 nitro-2-oxido-5-pentylphenylazo)-2-naphtholato))chroma	117527-94-3		403-720-7	
List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)					
	Chromium(III)compounds (as Cr)				
	WEL long-term (8-hr TWA reference period)	2	mg/m ³		
	Comments	IOELV			
4	hydrogen hydroxy[2-hydroxy-3-[(2-hydroxy-3-nitrobenzylidene)amino]-5-nitrobenzenesulphonato(3-)]chromate(1-), compound with 3-[(2-ethylhexyl)oxy]propylamine (1:1)	85455-32-9		287-267-9	
List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)					
	Chromium(VI)compounds(as Cr) Water Soluble				
	WEL long-term (8-hr TWA reference period)	0,01	mg/m ³		
	Comments	Carc.1B			
List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)					
	Chromium(VI)compounds(as Cr) Water Soluble				
	WEL long-term (8-hr TWA reference period)	0,05	mg/m ³		
	Comments	Carc.1B			

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	ethanol			64-17-5 200-578-6	
	dermal	Long term (chronic)	systemic	343	mg/kg/day
	inhalative	Long term (chronic)	systemic	950	mg/m ³
2	1-methoxy-2-propanol			107-98-2 203-539-1	
	dermal	Long term (chronic)	systemic	183	mg/kg/day
	inhalative	Long term (chronic)	systemic	369	mg/m ³
	inhalative	Short term (acut)	local	553,5	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	ethanol			64-17-5 200-578-6	
	oral	Long term (chronic)	systemic	87	mg/kg/day
	dermal	Long term (chronic)	systemic	206	mg/kg/day
	inhalative	Long term (chronic)	systemic	114	mg/m ³
2	1-methoxy-2-propanol			107-98-2 203-539-1	

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

oral	Long term (chronic)	systemic	33	mg/kg/day
dermal	Long term (chronic)	systemic	78	mg/kg/day
inhalative	Long term (chronic)	systemic	43,9	mg/m ³

PNEC values

No	Substance name	CAS / EC no	
	ecological compartment	Type	Value
1	ethanol	64-17-5 200-578-6	
	water	fresh water	0,96 mg/L
	water	Aqua intermittent	2,75 mg/L
	water	marine water	0,79 mg/L
	water	fresh water sediment	3,6 mg/kg dry weight
	water	marine water sediment	2,9 mg/L
	soil	-	0,63 mg/kg dry weight
	sewage treatment plant	-	580 mg/L
	secondary poisoning	-	0,38 mg/kg food
2	1-methoxy-2-propanol	107-98-2 203-539-1	
	water	fresh water	10 mg/L
	water	marine water	1 mg/L
	water	Aqua intermittent	100 mg/L
	water	fresh water sediment	52,3 mg/kg
	with reference to: dry weight		
	water	marine water sediment	5,2 mg/kg
	with reference to: dry weight		
	soil	-	4,59 mg/kg
	with reference to: dry weight		
	sewage treatment plant	-	100 mg/L

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Respirator A2

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material nitrile rubber
Material thickness >= 0.4 mm

Other

Protective work clothing. (EN 14605)

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form/Colour	
Various, depending on coloration	
Odour	
characteristic	
pH value	
No data available	
Boiling point / boiling range	
Value	78 °C
Source	supplier
Melting point/freezing point	
No data available	
Decomposition temperature	
No data available	
Flash point	
Value	13 °C
Source	supplier
Ignition temperature	
Value	255 °C
Source	supplier
Flammability	
No data available	
Lower explosion limit	
Value	1,3 % vol
Source	supplier
Upper explosion limit	
Value	15 % vol
Source	supplier
Vapour pressure	
Value	59 hPa
Source	supplier
Relative vapour density	
No data available	
Relative density	
No data available	
Density	
No data available	
Solubility in water	
Source	supplier
Comments	Not miscible or difficult to mix

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

Solubility	
No data available	

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
log Pow		-0,35	
Reference temperature		24	°C
with reference to		pH 7,4	
Method		OECD 107	
Source		ECHA	

Viscosity	
No data available	

Solvent content	
Value	82,5 %

Particle characteristics	
No data available	

9.2 Other information

Other information	
No data available.	

SECTION 10: Stability and reactivity

10.1 Reactivity

Dangerous reactions are not expected if the product is handled according to its intended use.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Oxidizing agents

10.6 Hazardous decomposition products

None, if handled according to intended use.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LD50		10470	mg/kg bodyweight
Species		rat	
with reference to		95% ethanol in water	
Method		OECD 401	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		4016	mg/kg bodyweight
Species		rat	
Method		EC 440/2008, B.1	

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

Source	ECHA
--------	------

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	440/2008/EC B.3.		
Source	ECHA		

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		124,7	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		
Method	EC 440/2008, B.4		
Source	ECHA		
Evaluation	non-irritant		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		
Evaluation/classification	Based on available data, the classification criteria are met.		
2	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		
Method	2004/73/EEC, B.5		
Source	ECHA		
Evaluation	non-irritant		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Route of exposure	respiratory tract		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure	Skin		
Species	mouse		
Source	ECHA		
Evaluation	non-sensitizing		

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

Evaluation/classification	Based on available data, the classification criteria are not met.		
2	1-methoxy-2-propanol	107-98-2	203-539-1
Route of exposure	Skin		
Species	guinea pig		
Method	440/2008/EC B.6		
Source	ECHA		
Evaluation	non-sensitizing		

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	in vitro gene mutation study in mammalian cells		
Species	mouse lymphoma cells		
Method	OECD 476		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	Genotoxicity in vivo		
Species	mouse		
Method	OECD 478		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Route of exposure	oral		
NOAEL			
Type of examination	2 generation study		
Species	mouse		
Method	OECD 416		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure	inhalational		
NOAEL	>=	20000	ppm
Type of examination	Prenatal Developmental Toxicity Study		
Species	rat		
Method	OECD 414		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

STOT - single exposure			
No data available			

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Route of exposure	oral		
Duration of exposure		14	week/s
Species	rat		

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

Target organ	kidneys
Method	OECD 408
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Aspiration hazard

No data available

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		14200	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	EPA		
Source	ECHA		

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
EC50		5012	mg/l
Duration of exposure		48	h
Species	Ceriodaphnia dubia		
Method	ASTM Standard E 729-80		
Source	ECHA		

Toxicity to Daphnia (chronic)

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
NOEC		9,6	mg/l
Duration of exposure		9	day(s)
Species	Daphnia magna		
Source	ECHA		

Toxicity to algae (acute)

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
EC50		275	mg/l
Duration of exposure		72	h
Species	Chlorella vulgaris		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Type	aerobic biodegradation		
Value	appr.	84	%
Duration		20	day(s)
Source	ECHA		
Evaluation	readily biodegradable		
2	1-methoxy-2-propanol	107-98-2	203-539-1
Type	aerobic biodegradation		
Value		96	%
Duration		28	day(s)
Method	OECD 301 E		
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
log Pow		-0,35	
Reference temperature		24	°C
with reference to	pH 7,4		
Method	OECD 107		
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	No data available.
vPvB assessment	No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	III
Hazard identification no.	30
UN number	UN1263
Proper shipping name	PAINT
Tunnel restriction code	D/E
Label	3

14.2 Transport IMDG

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	PAINT
EmS	F-E, S-E
Label	3

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	Paint
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
----	----------------	---------	--------	----

EU safety data sheet

Trade name: PIGMENTED LAQUER PEN 240

Current version : 2.0.0, issued: 01.04.2022

Replaced version: 2.0.0, issued: 18.11.2021

Region: IE

1	A mixture of: tert-alkyl(C12-C14)ammonium bis[1-[(2-hydroxy-5 nitrophenyl)azo]-2-naphthalenolato(2-)]-chromate(1-), tert-alkyl(C12 C14)ammonium ((1-(4(or 5)-nitro-2-oxidophenylazo)-2-naphtholato)(1-(3 nitro-2-oxido-5-pentylphenylazo)-2-naphtholato))chroma	117527-94-3	403-720-7	75
2	hydrogen hydroxy[2-hydroxy-3-[(2-hydroxy-3-nitrobenzylidene)amino]-5-nitrobenzenesulphonato(3-)]chromate(1-), compound with 3-[(2-ethylhexyl)oxy]propylamine (1:1)	85455-32-9	287-267-9	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:

P5b

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content

75,5 %

Other regulations

Adhere to the national sanitary and occupational safety regulations when using this product.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226

Flammable liquid and vapour.

H411

Toxic to aquatic life with long lasting effects.

H412

Harmful to aquatic life with long lasting effects.

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.